


MAXIMUM SHEAVE LOADS:
 LONGITUDINAL (0°) 2500kg
 TRANSVERSE (90°) 1750kg
 COMBINED 3750kg

MAX ROPE TENSION (kg)		
DEFLECTION	BISECTED ENTRY	STRAIGHT ENTRY
ANGLE 'A' (°)		
15	9580	9410
30	4830	4510
45	3270	2820
60	2500	1960
90	1770	1240



SHEAVE SPACING:
 STANDARD SHEAVE SPACING SHOWN.
 CUSTOM SPACING AVAILABLE IN 1.0MM INCREMENTS.

WEIGHT:
 527g (INCLUDING FULL LENGTH STAINLESS STEEL DECK FIXINGS)
 TITANIUM OPTION AVAILABLE (358g) - CONTACT SPINLOCK FOR MORE INFORMATION.

INSTALLATION:
 MOUNTING SURFACE MUST BE SUFFICIENTLY STRONG AND STIFF TO WITHSTAND COMPRESSIVE AND SHEAR FORCES EXERTED BY SHEAVE LOADING

spinlock
 BE ADVENTURE-PROOF



WARNING:
 IF USING AS TEMPLATE, ENSURE PRINTER SETTINGS ARE ADJUSTED TO ACCOUNT FOR THE DRAWING SCALE AND **ALWAYS** CHECK DIMENSIONS.



COPYRIGHT:
 THIS DRAWING IS PROTECTED BY COPYRIGHT. ANY USE IS FORBIDDEN WITHOUT THE WRITTEN CONSENT OF SPINLOCK.

ALL DIMENSIONS IN MM

SCALE

1:2

PAGE SIZE
 (297 x 210)

A4

DATE: OCT17

LINE SIZE: Ø15 MAX

FASTENERS: 3 x M8

MAX LOAD: SEE TABLE

TSR30L/3